

### 2016 Fiat 500L **SPECIFICATIONS**

Specifications are based on the latest product information available at the time of publication. All dimensions are in inches (millimeters) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

#### **GENERAL INFORMATION**

Vehicle Type	B-segment multipurpose vehicle (MPV)	B-segment multipurpose vehicle (MPV)	
EPA Vehicle Class	Small Station Wagon	_	
Assembly Plant	Kragujevac, Serbia	_	
Introduction Date	Mid-2013 as a 2014 model		

#### **BODY AND CHASSIS**

Layout	Transverse-mounted front engine, front-wheel drive
Construction	Unitized steel body

#### ENGINE: 1.4-LITER SOHC 16-VALVE TURBOCHARGED MULTIAIR INLINE FOUR-CYLINDER

Availability	Standard — 500L Pop, Easy, Trekking and Lounge models		
Type and Description	Inline four-cylinder, liquid-cooled, turbocharged		
Displacement	83.48 cu. in. (1,368 cu. cm)		
Bore x Stroke	2.83 x 3.31 (72 x 84)		
Valve System	Belt-driven, MultiAir, SOHC, 16 valves, hydraulic end-pivot roller rockers		
Fuel Injection	Sequential, multiport, electronic, returnless		
Construction	Cast-iron block with aluminum-alloy head and aluminum-alloy bedplate		
Compression Ratio	9.8:1		
Maximum Turbo Boost (psi / bar)	21 psi / 1.45 bar		
Power (SAE)	160 bhp (119 kW) @ 5,500 rpm (117 bhp/liter)		
Torque (SAE)	184 lbft. (250 N•m) @ 2,500-4,000 rpm		
Max. Engine Speed	6,500 rpm (electronically limited)		
Fuel Requirement	87 octane (R+M)/2 acceptable		
	91 octane recommended		
Oil Capacity	4.0 quarts (3.8 liters) with dry filter		
Coolant Capacity	4.6 quarts (14.4 liters)		
Emission Controls	Three-way catalytic converters, heated oxygen sensors and internal engine features <sup>(a)</sup>		
Max. Gross Trailer Weight	Not rated for trailer tow		
Emission Controls	Three-way catalytic converters, heated oxygen sense engine features <sup>(a)</sup>		



Estimated EPA Fuel Economy mpg (city/highway/combined)	25 / 33 / 28 with six-speed manual transmission
	24 / 33 / 27 with Euro Twin Clutch six-speed transmission
	22 / 30 / 25 with six-speed automatic transmission
Engine Assembly Plant	Termoli, Italy

<sup>(</sup>a) Meets Federal Tier 2 Bin 5 emission requirements and LEV III requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington.

### **C635 SIX-SPEED MANUAL TRANSMISSION**

Availability	Standard — 500L Pop, Easy and Trekking	
	1st, 2nd, 3rd gear: Triple Cone	
Description	4th and Reverse: Double Cone	
	5th, 6th gear: Single Cone	
Gear Ratios		
1st	4.154	
2nd	2.118	
3rd	1.361	
4th	0.978	
5th	0.756	
6th	0.622	
Reverse	4.00	
Final-drive Ratio	3.833	
Overall Top Gear	2.38	

### **C635 EURO TWIN CLUTCH SIX-SPEED TRANSMISSION**

Availability	Optional — 500L Pop	
Description	1st, 2nd gear: Double Cone	
	3rd, 4th, 5th, 6th gear: Single Cone	
Gear Ratios		
1st	4.154	
2nd	2.269	
3rd	1.435	
4th	0.978	
5th	0.755	
6th	0.622	
Reverse	4.00	
Final-drive Ratio	4.118	
Overall Top Gear	2.56	



A 11 = 1-114	Optional — 500L Easy and Trekking		
Availability	Standard — 500L Lounge		
Gear Ratios			
1st	4.04		
2nd	2.37		
3rd	1.56		
4th	1.16		
5th	0.85		
6th	0.67		
Reverse	3.19		
Final-drive Ratio	3.683		
Overall Top Gear	2.47		
Steering Turns (lock-to-lock)	3.0		
BRAKES			
Availability	Standard — all 500L models		
Front			

Availability	Standard — all 500L models	
Front		
Rotor size and type	12.0 x 1.10 (305 x 28) vented	
Caliper size and type	2.24 (57) single-piston with cast iron	
Swept area	345 sq. in. (876.1 sq. cm)	
Rear		
Rotor size and type	10.4 x 0.4 (264 x 10) solid	
Caliper size and type	1.49 (38) single-piston with aluminum housing	
Swept area	233 sq. in. (591.8 sq. cm)	
Chropi di ca	200 04. 111. (00 1.0 04. 011)	

### DIMENSIONS AND CAPACITIES(a)

Wheelbase	102.8 (2,612)	
Track, Front	59.1 (1,502)	
Track, Rear	59.4 (1,510)	
Overall Length	167.3 (4,249)	
	168.1 (4,270) — 500L Trekking	
Overall Width	69.8 (1,774) — without mirrors	
	80.2 (2,036) — with mirrors	
	70.9 (1,800 — 500L Trekking	



Overall Height	65.7 (1,670)	
Ground Clearance	4.7 (120)	
Drag Coefficient (Cd) (estimated)	0.310 — 500L Pop/Easy/Lounge	
	0.320 — 500L Trekking	
Curb Weight, lb. (kg) (estimated)	3,212 (1,457) — 500L with six-speed manual	
	3,262 (1,479) — 500L with six-speed Euro Twin Clutch	
	3,254 (1,476) — 500L with six-speed automatic	
Weight Distribution, percent F/R	60/40 — 500L with six-speed manual	
	60/40 — 500L with six-speed Euro Twin Clutch	
	60/40 — 500L with six-speed automatic	
Fuel Tank Capacity, gal. (liter)	13.2 (50)	

<sup>(</sup>a) All dimensions measured at curb weight with standard tires.

### **ACCOMMODATIONS**

ACCOMMODATIONS	
Seating Capacity, F/R	2/3
Front Seat	
Headroom	40.7 (1,034)
	40.5 (1,028) with dual-pane sunroof
Legroom	40.0 (1,015)
Shoulder room	57.3 (1,456)
Hip room	54.9 (1,394)
Total seat travel	8.3 (210) — driver
	9.0 (230) — passenger
EPA front row interior volume	54.0 cu. ft. (1.529 cu. m)
Rear Seat	
Headroom	38.7 (983)
	38.0 (966) with dual-pane sunroof
Legroom	36.7 (931)
Shoulder room	54.6 (1,388)
Hip room	49.4 (1,256)
Total seat travel	4.7 (120)
EPA second row interior volume	44.8 cu. ft. (1.268 cu. m)
Total Interior Volume	98.8 cu. ft. (2.797 cu. m)
EPA Luggage Compartment Volume	22.4 cu. ft. (0.633 cu. m)
EPA Volume behind front row (maximum cargo)	68.0 cu. ft. (1.927 cu. m)
EPA Interior Volume Index	121.1 cu. ft. (3.430 cu. m)
Trunk Liftover Height	25.9 (657)



_		_	$\hat{}$
	×	_	•

Availability	Standard — 500L Pop, Easy and Lounge
Size and Type	205/55R16 BSW All-season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2 or Nexen CP671 Classe Premiere
Revs per mile (km)	836 (519)
Availability	Standard — 500L Trekking
	Included with 17-in. wheels on 500L Lounge
Size and Type	225/45R17 BSW All-Season
Mfr. and Model	Continental Conti ProContact or Goodyear Eagle LS2 or Nexen CP671 Classe Premiere
Revs per mile (km)	832 (517)
WHEELS	
Availability	Standard — 500L Easy and 500L Lounge
Type and Material	Cast-aluminum, 13-spoke radial design, fully painted Argento
Size	16 x 6.5 in.
Availability	Optional — 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, oval-twist design, painted Argento with Grigio (gray) pockets
Size	16 x 6.5 in.
Availability	Standard — 500L Trekking
Type and Material	Cast-aluminum, seven-hole design, machined face with painted Grigio pockets
Size	17 x 7.0 in.
Availability	Optional — 500L Lounge and 500L Trekking
Type and Material	Cast-aluminum, five-oval design, painted Argento with Grigio pockets
Size	17 x 7.0 in.
Availability	Optional — 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, dual-twist design, painted Argento with Nero (black) pockets (must have optional Nero painted roof)
Size	17 x 7.0 in.



Availability	Optional — 500L Lounge
Type and Material	Cast-aluminum, seven-spoke, dual-twist design, painted Argento with Bianco (white) pockets (must have optional Bianco painted roof)
Size	17 x 7.0 in.

