



2016 FIAT 500 / 500c SPECIFICATIONS

2016 Fiat 500 / 500c SPECIFICATIONS

*Specifications are based on the latest product information available at the time of publication.
All dimensions are in inches (millimeters) unless otherwise noted.
All dimensions measured at curb weight with standard tires and wheels.*

GENERAL INFORMATION

Vehicle Type	A-segment hatchback (500) or cabrio (500c)
EPA Vehicle Class	Mini-compact
Assembly Plant	Toluca, Mexico
Introduction Date	Spring 2011 as a 2012 model

BODY AND CHASSIS

Layout	Transverse-mounted front engine, front-wheel drive (FWD)
Construction	Unitized steel body

ENGINE: 1.4-LITER MULTIAIR I-4

Availability	Standard — Fiat 500 and 500c Pop, Sport and Lounge
Type and Description	Inline four-cylinder, liquid-cooled
Displacement	83.48 cu. in. (1,368 cu. cm)
Bore x Stroke	2.83 x 3.31 (72.0 x 84.0)
Valve System	Belt-driven, MultiAir, SOHC, 16 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Cast iron block with aluminum-alloy heads and aluminum-alloy bedplate
Compression Ratio	10.8:1
Power (SAE net)	101 hp (75 kW) @ 6,500 rpm (73.8 bhp/liter)
Torque (SAE net)	97 lb.-ft. (132 N•m) @ 4,000 rpm
Max. Engine Speed	6,900 rpm (electronically limited)
Fuel Requirement	87 octane (R+M)/2 acceptable 91 octane recommended
Oil Capacity	4.0 quarts (3.8 liters) with dry filter
Coolant Capacity	4.6 quarts (14.4 liters)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features ^(a)
Max. Gross Trailer Weight	Not rated for trailer tow



2016 FIAT 500 / 500c SPECIFICATIONS

EPA Fuel Economy mpg (city/hwy)	Fiat 500 Pop, Sport and Lounge: 31/40 (five-speed manual) 27/34 (six-speed automatic)
	Fiat 500c Pop and Lounge: 31/40 (five-speed manual) 27/34 (six-speed automatic)

Engine Assembly Plant	Dundee, Mich.
-----------------------	---------------

(a) Meets Federal Tier 2 Bin 5 emission requirements and LEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington.

ENGINE: 1.4-LITER TURBOCHARGED MULTIAIR I-4

Availability	Standard — Fiat 500 Turbo
Type and Description	Inline four-cylinder, liquid-cooled, turbocharged
Displacement	83.48 cu. in. (1,368 cu. cm)
Bore x Stroke	2.83 x 3.31 (72.0 x 84.0)
Valve System	Belt-driven, MultiAir, SOHC, 16 valves, hydraulic end-pivot roller rockers
Fuel Injection	Sequential, multiport, electronic, returnless
Construction	Cast-iron block with aluminum-alloy head and aluminum-alloy bedplate
Compression Ratio	9.8:1
Maximum Turbo Boost (psi / bar)	18 psi / 1.24 bar
Power (SAE)	135 hp (101 kW) @ 5,500 rpm (98.7 bhp/liter)
Torque (SAE)	150 lb.-ft. (203 N•m) @ 2,400-4,200 rpm
Max. Engine Speed	6,500 rpm (electronically limited)
Fuel Requirement	87 octane (R+M)/2 acceptable 91 octane recommended
Oil Capacity	4.0 quarts (3.8 liters) with dry filter
Coolant Capacity	4.6 quarts (14.4 liters)
Emission Controls	Dual three-way catalytic converters, heated oxygen sensors and internal engine features ^(a)
Max. Gross Trailer Weight	Not rated for trailer tow
Estimated EPA Fuel Economy mpg (city/highway/combined)	28 / 34 / 31
Engine Assembly Plant	Dundee, Mich.

(a) Meets Federal Tier 2 Bin 5 emission requirements and LEV II requirements in California, Massachusetts, New York, Maine, Vermont, Connecticut, Pennsylvania, Rhode Island, New Jersey, Oregon and Washington.



2016 FIAT 500 / 500c SPECIFICATIONS

TRANSMISSION: C514 FIVE-SPEED MANUAL

Availability	Standard — 500 and 500c Pop, Sport and Lounge
Description	1st, 2nd gear: Double Cone 3rd, 4th, 5th, gear: Single Cone
Gear Ratios	
1st	3.909
2nd	2.174
3rd	1.345
4th	0.974
5th	0.766
Reverse	3.818
Final-drive Ratio	3.44 (500 and 500c Pop and Lounge) 3.73 (500 Sport)
Overall Top Gear	2.63 (500 and 500c Pop and Lounge) 2.85 (500 Sport)

TRANSMISSION: AISIN AUTOMATIC SIX-SPEED OVERDRIVE WITH AUTO STICK

Availability	Optional — 500 and 500c Pop, Sport, Turbo and Lounge
Description	Auto Stick driver-interactive manual control and electronically modulated torque converter clutch
Gear Ratios	
1st	4.044
2nd	2.371
3rd	1.556
4th	1.159
5th	0.852
6th	0.672
Reverse	3.193
Final Drive Ratio	4.103
Overall Top Gear	2.76



2016 FIAT 500 / 500c SPECIFICATIONS

TRANSMISSION: C510 PERFORMANCE FIVE-SPEED MANUAL

Availability	Standard — 500 Turbo
Description	1st, 2nd gear: Double Cone 3rd, 4th, 5th, gear: Single Cone
Gear Ratios	
1st	3.909
2nd	2.238
3rd	1.520
4th	1.156
5th	0.872
Reverse	3.909
Final-drive Ratio	3.353
Overall Top Gear	2.92

ELECTRICAL SYSTEM

Alternator	105-amp — Standard on 500 Pop (with automatic transmission) and 500c Pop, Sport and Lounge 120-amp — Standard on 500 Pop (with manual transmission) and Turbo
Battery	500 CCA, maintenance free

SUSPENSION

Front	MacPherson suspension, coil spring with twin-tube shock absorbers and stabilizer bar — included with 500 Pop and Lounge Sport-tuned shock absorbers and springs — included with 500 Sport Sport-tuned shock absorbers, springs and performance-designed lower-control arm — included with 500 Turbo
Rear	Rear twist-beam axle with coil springs and twin-tube shock absorbers — included with 500 Pop and 500 Lounge Sport-tuned shock absorbers and springs — included with 500 Sport and Turbo

STEERING

Type	Power rack and pinion with electric power steering (EPS) column
Overall Ratio	16.3:1
Turning Diameter (curb-to-curb)	30.6 ft. (9.32 m)
Steering Turns (lock-to-lock)	3.0



2016 FIAT 500 / 500c SPECIFICATIONS

BRAKES

Availability	Standard — 500 and 500c Pop and Lounge, 500 Sport
Front	
Rotor size and type	10.1 x 0.86 (257 x 22) vented
Caliper size and type	2.12 (54) single-piston with aluminum housing
Swept area	193 sq. in. (1,244 sq. cm)
Rear	
Rotor size and type	9.4 x 0.4 (240 x 11) solid
Caliper size and type	1.33 (34) single-piston with aluminum housing
Swept area	153 sq. in. (984 sq. cm)
Availability	Standard — 500 Turbo
Front	
Rotor size and type	11.1 x 0.86 (282 x 22) vented
Caliper size and type	2.12 (54) single-piston with aluminum housing
Swept area	193 sq. in. (1,244 sq. cm)
Rear	
Rotor size and type	9.4 x 0.4 (240 x 11) solid
Caliper size and type	1.33 (34) single-piston with aluminum housing
Swept area	153 sq. in. (984 sq. cm)

DIMENSIONS AND CAPACITIES^(D)

Wheelbase	90.6 (2,300)
Track, Front	500 — 55.4 (1,406.8) 500c — 55.4 (1,406.8) 500 Turbo — 55.4 (1,406.8)
Track, Rear	500 — 55.0 (1,397.0) 500c — 55.0 (1,397.0) 500 Turbo — 55.0 (1,397.0)
Overall Length	500 — 139.6 (3,546.7) 500c — 139.6 (3,546.7) 500 Turbo — 144.4 (3,667.3)
Overall Width	64.1 (1,627.0)
Overall Height	500 — 59.8 (1,519) 500c — 59.8 (1,519) 500 Turbo — 59.8 (1,519)



2016 FIAT 500 / 500c SPECIFICATIONS

Ground Clearance	500 Pop — 4.5 (114)
	500 Sport and Lounge — 4.5 (114)
	500c — 4.6 (118.0)
	500 Turbo — 4.5 (114)
Drag Coefficient (Cd)	500 Pop — 0.332
	500 Sport — 0.362
	500 Lounge — 0.359
	500c Pop and Lounge — 0.364
	500 Turbo — 0.362
Curb Weight, lb. (kg)	500 with five-speed manual — 2,366 (1,074)
	500 with six-speed automatic— 2,452 (1,112)
	500c with five-speed manual — 2,424 (1,099)
	500c with six-speed automatic— 2,511 (1,139)
	500 Turbo with five-speed manual — 2,505 (1,136)
	500 Turbo with six-speed automatic — 2,576 (1,168)
Weight Distribution, % F/R	500 with five-speed manual — 63/37
	500 with six-speed automatic — 65/35
	500c with five-speed manual — 62/38
	500c with six-speed automatic — 64/36
	500 Turbo with five-speed manual — 65/35
	500 Turbo with six-speed automatic — 66/34
Fuel Tank Capacity, gallon (liter)	10.5 (40)

(d) All dimensions measured at curb weight with standard tires.

ACCOMMODATIONS

Seating Capacity, F/R	2/2
Front Seat	
Headroom	500 — 38.9 (989.1)
	500 with sunroof — 37.6 (956.3)
	500c — 38.6 (980)
Legroom	40.7 (1,034.8)
Shoulder room	49.4 (1,254.8)
Hip room	47.9 (1,215.4)
Total seat travel	Driver — 8.2 (210.0)
	Passenger — 8.2 (210.0)
EPA front row interior volume	500 — 45.3 cu. ft. (1.282 cu. m)
	500c — 44.9 cu. ft. (1.272 cu. m)



2016 FIAT 500 / 500c SPECIFICATIONS

Rear Seat	
Headroom	500 — 35.6 (902.9) 500c — 36.8 (934)
Legroom	31.7 (805.1)
Shoulder room	46.4 (1,177.5)
Hip room	42.6 (1,083.1)
EPA second row interior volume	500 — 30.2 cu. ft. (0.854 cu. m) 500c — 31.3 cu. ft. (0.887 cu. m)
Total Passenger Interior Volume	500 — 75.5 cu. ft. (2.137 cu. m) 500c — 76.2 cu. ft. (2.159 cu. m)
EPA Luggage Compartment Volume	500 — 9.5 cu. ft. (0.269 cu. m) 500c — 5.4 cu. ft. (0.152 cu. m)
EPA Interior Volume Index	500 — 84.9 cu. ft. (2.405 cu. m) 500c — 81.6 cu. ft. (2.311 cu. m)
Trunk Lifter Height	27.7 (703.6)

WHEELS

Availability	Standard — 500 and 500c Pop
Type and material	Steel wheels with Tech Silver painted wheel covers
Size	15 x 6.0
Availability	Standard — 500 and 500c Easy
Type and material	Cast-aluminum, five-oval spoke design, fully painted Tech Silver
Size	15 x 6.0
Availability	Standard — 500 and 500c Lounge
Type and material	Cast-aluminum, nine split-spoke design, fully painted Satin Carbon
Size	15 x 6.0
Availability	Optional on 500 and 500c Lounge
Type and material	Cast-aluminum, polished face with Tech Silver painted pockets
Size	15 x 6.0
Availability	Standard — 500 Sport
Type and material	Cast-aluminum, polished face with Dark Mineral Gray painted pockets
Size	16 x 6.5



2016 FIAT 500 / 500c SPECIFICATIONS

Availability	Standard — 500 Turbo
Type and material	Cast-aluminum, polished face with Gloss Black painted pockets
Size	16 x 6.5

Availability	Optional — 500 Sport
Type and material	Cast-aluminum, five split-spoke design with Bright Silver face and Rosso accented center cap
Size	16 x 6.5

Availability	Optional — 500 Turbo
Type and material	Cast-aluminum, five split-spoke design with Hyper Nero face and Rosso accented center cap
Size	16 x 6.5

TIRES

Availability	Standard — 500 Pop, Easy and Lounge
Size and type	185/55R15 BSW All-season
Mfr. and model	Continental ContiProContact or Firestone Firehawk GTH or Pirelli Cinturato P7 A/S
Revs per mile (km)	906 (563)

Availability	Standard — 500 Sport and Turbo
Size and type	195/45R16XL BSW All-season
Mfr. and model	Pirelli Cinturato P7 A/S or Continental ContiProContact
Revs per mile (km)	901 (560) or 911 (566)

